

## Hi-Tech-600™

## Nitrile Rubber Through-the-Weave Construction

## Hi-Tech 600™ FEATURES

- 100% synthetic reinforcement, totally encapsulated in a nitrile rubber compound utilizing a through-the-weave process.
- A medium duty rubber hose construction with good heat and chemical resistance.
- The hose is made in the European Union to NAFH specifications, and the couplings are Made in USA.
- The performance of the hose and couplings shall meet and exceed NFPA 1961 Standards.
- · Available in yellow and red color only.

Applications: Attack, High Rise and Forestry

Available in 50 and 100 foot lengths





HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 50' UNCPLD
1½"	HIT-600	600 PSI	300 PSI	13/4"	14 lbs.
1 3/4"	HIT-600	600 PSI	300 PSI	2"	17 lbs.
2½"	HIT-600	600 PSI	300 PSI	213/16"	24 lbs.
3"	HIT-600	600 PSI	300 PSI	33/8"	36 lbs.

HIT-600,™ Hi-Tech-600,™ are trademarks of North American Fire Hose Corporation. All rights reserved.

Revision 2019A

## **NORTH AMERICAN FIRE HOSE**

910 East Noble Way • Santa Maria, CA 93454 Tel: 805.922.7076 • Fax: 805.922.0086 NAFHC.com